### **DEEP SUBSURFACE / WATER RESISTANT DENSIFIER / HIGHLY ABRASION RESISTANT**

# GREENUMBRELLA® HYDROSHIELD

## **Resisting Water & Filling the Voids** Green Umbrella<sup>®</sup> HydroShield<sup>™</sup> concrete hardener and densifier. Reaching deep within the subsurface, Hydro-

Shield creates more than a conventional shell surface. The unique formulation is resistant to surface water and breathable—resulting in a bond within the concrete that is stronger, denser, and less porous. A clear, odorless solution specially formulated to be a CrossOver<sup>™</sup> densifier designed for application *@EarlyAge<sup>™</sup>*, *@Profile&Polish<sup>™</sup>*, or *@MatureAge<sup>™</sup>* concrete. Unlike conventional hardeners, HydroShield is a S.O.L.O.<sup>1</sup> treatment that requires one application and no scrubbing or mopping. HydroShield produces a substrate that will stain less and

wear longer, reducing maintenance frequency and extending the concrete's life cycle.



#### **CUT LABOR**

CUTSHEET

- S.O.L.O<sup>1</sup> application & R.T.U.<sup>2</sup> treatment
- Densifies & resists water in a single treatment
- No scrubbing or agitation required during application

#### **VERSATILE ARCHITECTURAL APPLICATIONS**

Ideal for **interior** or **exterior**, vertical or horizontal in Demanding Applications; warehouse/distribution centers, food service, parking decks, garages, hospitals, or similar & specifically for water resistant Decorative Color Applications; retail spaces & showrooms, restaurants, offices, lobby areas, museums, municipalities, airports, hospitals, schools, fire-stations, or most concrete surfaces.

#### **EASY TO INSTALL - SIMPLE TO MAINTAIN**

HydroShield is shipped R.T.U<sup>2</sup>. Easily apply S.O.L.O.<sup>1</sup> with a

GU recommended sprayer for coverage of 400-600 SF per

gallon, in some applications spread with GU exploded-tip

broom or T-Bar. To maintain, simply damp mop, auto

scrub, and periodically burnish using Green Umbrella Life

 $\bigcirc$ 

#### **CUT DOWNTIME**

- 30 minute dwell time, short dry time
- 3 hour to all traffic & abrasive profile
- Optional same-day, after concrete placement—no 28-day application restriction



#### CUT ENVIRONMENTAL IMPACT

- Alternative to off-gassing flooring
- Extends life cycle of concrete
- No VOC

<sup>1</sup>Spray-On, Leave-On <sup>2</sup>Ready-To-Use



Cycle<sup>™</sup> maintenance system treatments.



Rev.12/20 © 2006 Made in the USA

