



MAXDEFENSE




HARDENER:
DRY SHIELD

GRIND
HONE



The first line of defense is Green Umbrella Dry Shield™. Increases hardness, while reducing porosity. Requires no rinsing & disposal and will not gel on surface — can be allowed to air dry. Stands up to heavy abrasion and foot traffic while providing excellent slip resistance. Has the highest abrasion resistance. Due to being pH neutral Green Umbrella Dry Shield™ does not interfere with the application of concrete dyes as sodium products can. Decreases black tire marking from lift trucks and other equipment.

the application of concrete dyes as sodium products can. Decreases black tire marking from lift trucks and other equipment.



CHLORIDE SCREEN:
SHIELD & ENHANCE

HONE



The second line of defense, Green Umbrella Shield & Enhance™ is an environmentally friendly densifier that deeply penetrates and chemically reacts with concrete to create a floor exceptionally resistant to the damaging effects of water and salt with up to 91% chloride prevention. Green Umbrella Shield & Enhance™ has met and exceeded 244 lab testing requirements. Green

Umbrella Shield & Enhance™ is specially engineered to enhance the natural beauty of polished or dyed & polished concrete, providing a deeper and richer appearance to any concrete surface that has been ground, honed and polished.



PENETRATING TREATMENT:
MICROFILM

POLISH



The added protection that makes you shine. Green Umbrella Microfilm™ is an environmentally friendly hybrid surface treatment that creates a durable micro-thin layer to seal polished concrete. Properly applied, Green Umbrella Microfilm™ forms a breathable, dense, protective layer which is highly resistant to aviation oils, stands up to acid and chemical exposure, and is not

prone to whitening, peeling or flaking — with a beautiful high-gloss finish. Testing results prove superior chemical resistance to some of the harshest chemistries a facility floor will face. It is the repairable layer to the Green Umbrella Max Defense Treatment System™ in case burnishing would not remove etching, simply reapply.

EQUIPMENT NEEDED

ABRASIVES NEEDED

