CUTSHEET

HORIZONTAL - VERTICAL - OVERHEAD / 10K+PSI / QUICK TO TRAFFIC



Not a Patch. It's Permanent. Green Umbrella® PCR®, designed for permanence, not just a temporary fix or patch. Permanent Concrete Repair is an industry-leading, high early strength, zero-shrink, water-proof component that can be applied in half the time of

tradition patch products. PCR[®] establishes a unique, tenacious bond for horizontal, vertical, or overhead repairs. Repair cracks, spalling, or trip-hazards with structural strength. Stop the replacement cycle! PCR[®] is a permanent, economical repair, reducing/eliminating costly concrete replacement.



CUT LABOR

- Install quickly and easily.
- Eliminates demolition/full replacement.
- One-time install. No laborious bond coats or sealers needed.



CUT DOWNTIME

- Applied in half the time of other industry products.
- PCR repairs have industry leading completion times: Foot traffic 60 minutes. Vehicle traffic in 2 hours.
- Accomplish permanent repair in hours, saving the time and expense of demolition and replacement.



CUT ENVIRONMENTAL IMPACT

- Restore existing concrete without costly demolition and replacement.
- Reduce the carbon footprint by rejuvenating existing concrete and eliminating landfill hazardous waste.

VERSATILE ARCHITECTURAL APPLICATIONS

For use in sidewalks, docks, bridges, roadways, driveways, stairs, potholes, industrial floors, parking decks, airport runways, and more.

EASY TO INSTALL - SIMPLE TO MAINTAIN

In a clean & dry container - introduce liquid activator PCR PART TWO followed by a dry mix PCR PART ONE. Mix to the desired slump and apply using a trowel. For detailed application instructions see PCR Application Sheet. [Note: An Accelerator, Retarder, and/or filler Aggregate may also be required. See PCR Application Sheet for details.] Install PCR only on clean & dry concrete surfaces. Install PCR at thicknesses varying from 1/16" to several inches. Versatile finish options: smooth finish, stamped or broomed. PCR will set from 10-30 min. Foot traffic at 60 min., all other traffic after 2 hours. After installation, PCR requires no special coating or maintenance.







Rev. 11/20 © 2020 Made in the USA