SUBSURFACE / HYBRID EVAPORATING MEMBRANE CURE & HARDENER / SINGLE APPLICATION

GREEN UMBRELLA° SoloCure

PENETRATING DENSIFICATION

ing curing compound and densifier that meets ASTM C-309; & PROTECTIVE CURE this S.O.L.O. formula can be applied on @EarlyAge slabs immediately after place and finish. One of the most innovative products on today's market,

Green Umbrella® SoloCure™ is a water-based, membrane-form-

SoloCure saves time and money during placement by replacing multiple products with one easy-to-use application. This product is specifically designed for concrete that needs long-term protection against heavy wear & abuse without the high VOC content in conventional products. The membrane will form on the surface of the concrete restricting moisture from evaporating while allowing the hardener to penetrate deep into the matrix for improved control over both curing times and strengthening properties.

VERSATILE ARCHITECTURAL APPLICATIONS

Ideal for interior or exterior, vertical or horizontal concrete, precast or cementitious surfaces. Demanding Applications, warehouse/distribution centers, food service, parking decks, garages, hospitals, or similar, retail spaces & showrooms, restaurants, business offices, lobby areas, museums, municipalities, airports, hospitals, schools, fire-stations, parking lots, or most concrete surfaces.



CUT LABOR

- S.O.L.O.* Applications and R.T.U.**
- Enhances lifecycle, reducing future repairs
- @EarlyAge membrane forming cure and densifier, reducing construction mobilizations



CUT DOWNTIME

- @EarlyAge sealer, provides early protection
- Short dry time
- 3 hours to traffic



CUT ENVIRONMENTAL IMPACT

- Product reduction 2 in 1 Cure & Densifier
- Extends life cycle of concrete
- Increased abrasion resistance

5/PAIL *Spray-On, Leave-On **Ready-To-Use

EASY TO INSTALL - SIMPLE TO MAINTAIN

Shipped R.T.U.** In case of separation, mix. Easily apply S.O.L.O. with a GU recommended re-circulating pump and sprayer for coverage of 200-600 sq.ft. per gallon. Keep substrate wet, placing SoloCure™ uniformly and without puddling. To remove film-forming cure use only Deep-Clean w/Slip Resist cleaner by auto scrubber equipped with soft bristle brushes or thick black pad after 28 days. For additional sheen and daily cleaning use DeepClean & Maintain and burnish with a propane powered UHS GreenGloss

concrete weighted burnisher with a thick black pad.







